

**Stain Proof. Bleachable.  
Cleanable. Worry Free.**

Tedlar™ Wallcoverings are protected by a film that provides an impervious barrier against stains. Tedlar™ Wallcoverings can stand up to industrial cleaning products including bleach without discoloration. So when accidents happen, your wallcoverings look good regardless.





**The Iodine and Acetone Test**



One drop of Iodine was placed on the surface of the wallcovering and left for an hour. It was then wiped away with a dry cloth. Afterwards the surface was wiped using nail polish remover.

The iodine on the standard wallcovering soaks into the surface and is unwashable unlike the Tedlar™ which beads on the surface and wipes away clean. The nail polish remover damages the surface of the standard wallcovering and still does not remove the iodine while the Tedlar™ wallcovering remains intact.

**TEDLAR™ Wallcoverings**



**Standard Type II Wallcoverings**



## Safe for Important Environments



### Mold, Mildew, and Bacteria

Bacteria does not degrade Tedlar™ film, nor does the film provide nutrients to assist bacterial growth. Tedlar™ Wallcoverings are certified by the MicroStar Labs, Chicago, IL, to pass ASTM G21 and JIS Z 2801.



### Fire and Smoke

Tedlar™ film has low smoke ratings and does not readily burn or support combustion. Exceeding the ASTM E84 Class A rating, it is one of the safest materials designed for interiors.

## Durable

Tedlar™ Wallcoverings offer exceptional scrubbability and abrasion resistance. Tedlar™ Wallcoverings offers Type III surface protection in a Type II weight.

Property	Section Reference	Category V Type II Commercial Serviceability	Tedlar™ Wallcoverings	Category VI Type III Commercial Serviceability
Minimum colorfastness	7.3	200h	Excellent	200 h
Minimum scrubbability	7.7	300 cycles	Passes 500 cycles	500 cycles
Minimum abrasion resistance (220 grit)	7.8	300 cycles	Passes 1000 cycles	1000 cycles
Minimum breaking strength: MD (machine direction)	7.9	50 lb [22.7 kg]	106 lb (Passes)	100 lb [45.4 kg]
Minimum breaking strength: CMD (cross machine direction)	7.9	55 lb [24.9 kg]	129 lb (Passes)	95 lb [43.1 kg]
Minimum tear resistance Elmendorf Tear Scale (MD/CMD)	7.10	25/25	76.2/>100 (Passes)	50/50
Maximum blocking resistance	7.11	< 2	1 (Passes)	< 2

## Tedlar™ Wallcoverings Staining Agents and Cleaning Methods

All products were applied to Tedlar™ Wallcoverings and allowed to set for 24 hours. Utilizing the following methods, all products were successfully removed from the Tedlar™ wallcoverings.

### Dry Cloth Cleaning

Acid Solutions\*  
Acetone  
Butanone  
Ethylalcohol  
Gasoline  
Glycol  
Toluene

### Wet Cloth Cleaning

Coffee  
Grape Juice  
Mustard Sauce  
Red Wine  
Tea Stains  
Worcestershire Sauce  
Chocolate Syrup  
Brake Fluid  
Iodine  
Sodium Hydroxide

### Detergent

Ketchup  
Black Crayons  
Brown Shoe Polish  
Lipstick  
Whire Board Marker  
Oily Pen  
Asphalt  
Mercurochrome

### Solvent

Ball Point Pen  
Spray Paint

\*Acid Solutions include: Acetic acid, 10% nitric acid, 20% hydrochloric acid, and 30% sulfuric acid

[tedlarwallcoverings.dupont.com](http://tedlarwallcoverings.dupont.com)

**DUPONT™ TEDLAR™ WALLCOVERINGS**

*Style that Endures™*



Copyright © 2018 DuPont. All rights reserved. The DuPont Oval Logo, DuPont™, Style that Endures™ and Tedlar™ are trademarks or registered trademarks of E.I. du Pont de Nemours and Company or its affiliates. K-XXXXX.